

除雪グレーダ

規格		3.7m級		4.0m級		4.3m級		3.7m級		4.0m級		4.3m級	
メーカー		コマツ						キャタピラー					
型式		GD675-6						12M3 AWD					
国内排出ガス規制適合		2014年排ガス規制適合						2014年排ガス規制適合					
車両総質量 [kg]		18,265		18,335		18,465		18,275		18,490		18,555	
前輪荷重 [kg]		5,465		5,495		5,565		4,710		4,765		4,870	
後輪荷重 [kg]		12,800		12,840		12,900		13,565		13,725		13,685	
全長 [mm]		9,765		9,765		9,765		8,910		8,910		8,910	
全幅 [mm]		2,410		2,410		2,410		2,595		2,595		2,595	
全高 [mm]		3,410		3,410		3,410		3,310		3,310		3,310	
軸間距離 [mm]		6,495		6,495		6,495		6,125		6,125		6,125	
定格出力 [kW]		135~163(可変出力)		135~163(可変出力)		135~163(可変出力)		141~188(可変出力)		141~188(可変出力)		141~188(可変出力)	
走行速度 [km/h]	速度段	前進	後進	前進	後進	前進	後進	前進	後進	前進	後進	前進	後進
	1	3.8	5.0	3.8	5.0	3.8	5.0	4.1	3.2	4.1	3.2	4.1	3.2
	2	5.5	10.2	5.5	10.2	5.5	10.2	5.5	6.0	5.5	6.0	5.5	6.0
	3	7.7	22.3	7.7	22.3	7.7	22.3	8.0	8.7	8.0	8.7	8.0	8.7
	4	11.2	44.0	11.2	44.0	11.2	44.0	11.0	13.5	11.0	13.5	11.0	13.5
	5	16.9	-	16.9	-	16.9	-	17.1	25.3	17.1	25.3	17.1	25.3
	6	24.5	-	24.5	-	24.5	-	23.3	36.8	23.3	36.8	23.3	36.8
	7	33.7	-	33.7	-	33.7	-	32.0	-	32.0	-	32.0	-
8	48.5	-	48.5	-	48.5	-	46.6	-	46.6	-	46.6	-	
最大けん引力 [N]		100,420		100,730		101,200		-		-		-	
最小旋回半径 [m]		7.4		7.4		7.4		7.6		7.6		7.6	
ブレード荷重 [N]		88,910		89,400		90,540		-		-		-	
作業装置	全幅 [mm]	3,710		4,010		4,265		3,700		4,000		4,300	
	全高 [mm]	545		545		580		555		620		620	
	厚さ [mm]	19		19		25		22		25		25	
タイヤ		14.00-24, 16PR		14.00-24, 16PR		14.00-24, 16PR		14.00R-24		14.00R-24		14.00R-24	